



Description

The PT-300 is a hot-pressing device designed for joining Habasit driving and conveyor belts up to 300 mm wide and 8 mm thick, using the Thermofix procedure. The heated bottom pressure plate is fitted with a removable setting plate with clamping bars for securely fixing the belt ends. The pressure is produced by means of a threaded spindle and torque wrench. The hot-pressing device PT-300 is suitable for both workshop and portable use.

Technical data			
Joining System	Thermofix		
Belt/tape width max.	300 mm		12 inch
Belt/tape width max. For joining angle of 75°	250 mm		10 inch
Belt/tape width max. for joining angle of 60°	200 mm		8 inch
Belt/Tape thickness max.	8 mm		0.31 inch
Dimensions (LxWxH)	420 x 175 x 200 mm		16.50 x 6.90 x 7.90 inch
Max. skiving length	110 mm		4 inch
Cooling media	Ambient air		
Adjustable Temperature	Switchable		
Temperature range	min. 100 °C		min. 212 °F
	max. 120		max. 248
Weight net	12.00 kg		26.50 lb

Available versions	Item number	Power supply	Power
PT-300/6	H080690290	1ph 120V 60Hz	800W
PT-300/8	H080690310	1ph 230V 50Hz	800W

Group GFT Tools
 Sub-Group Hot pressing devices
 Customs tariff number 85158090



Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.