

# Spindle Tapes

## TS-55



### Main industry segments



Paper manufacturing, Paper manufacturing and processing, Yarn processing

### Applications

Machine tape, Spindle drive

### Special features

Abrasion resistant, Anti-static, Constant coefficient of friction, Constant coefficient of friction during service life, For spindle braking, Low elasticity



Product Construction / Design	
Spindle side material	Polyamide (PA)/Cotton (CO) fabric as friction cover (whirl side)
Spindle side surface	Fabric
Spindle side color	Yellow
Traction layer (material)	Polyamide (PA) foil
Pulley side material	Acrylonitrile-Butadiene-Rubber (NBR) as friction cover (pulley/cylinder side)
Pulley side surface	Sand finish
Pulley side color	Green

Product characteristics	
Drive determination	1- / 2- / or 4-spindle ring spinning frames
Antistatically equipped	Yes
Adhesive free joining method	No

Technical data			
Thickness of belt	0.85 mm	0.03 inch	
Mass of belt (belt weight)	0.80 kg/m <sup>2</sup>	0.164 lb/sqft	
Tensile force for 1% elongation (k1% after running in) per unit of width (Habasit standard SOP3-013):	2.4 N/mm	14 lbf/in	
Nominal peripheral force per unit of width	6.5 N/mm	37 lbf/in	
Min. operating temperature admissible (continuous)	-20 °C	-4 °F	
Max. operating temperature admissible (continuous)	100 °C	212 °F	
Seamless manufacturing width	1200 mm	47 inch	

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

### Joining related properties

[Link to JDS:](#)

Joining method	Unit	Thermofix
Pulley diameter (minimum)	mm inch	25 0.98
Pulley diameter minimum with counter flection	mm inch	25 0.98

### Chemical resistance

Link to 'Chemical resistance information': <http://www.habasit.com/en/chemical-resistance.htm>

### Mode of use or conveyance

Power transmission, Spindle drive

### Calculations

With power transmission belts a calculation at least of the belt width and initial elongation is highly recommended. For this serves the Habasit SeleCalc calculation program. The easiest way is to have belt drives calculated by Habasit representatives.

### Recommendation

Observe the indications of the machine handbook from the machine manufacturers

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit, Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 94/9) and therefore is subject to user's analysis in the respective environment, When changing the direction of rotation (S/Z direction of rotation) the spindle tape can run off the driving pulley

Group	Polyamide Spindle Tapes
Sub-Group	TS Polyamide Spindle Tapes
Item number	H010100232
Customs tariff number	40103900

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.